

# AquaPure™ Quick Drop

Aquapure Quick Drop is a proprietary blend of clay minerals, polymer and pH adjusting agents which allow entrapment or encapsulation of emulsified oils and precipitated metals from various wastewater streams. This one-step system offers a simple alternative to multiple tank treatments while ensuring that the treated effluent will meet POTW discharge limits established by local and state authorities. Aquapure Quick Drop captures solids and masses them together to quickly settle suspended particulate. The use of this product requires vigorous mixing.

## Features & Benefits

|                               |   |
|-------------------------------|---|
| Granulated clay blend         | Long shelf life, no odor                            |
| One step coagulant/flocculant | Quickly masses and drops TSS                        |
| Bentonite blend               | Highest coefficient of expansion for massing solids |

## Typical Applications

- Works well on tubbing wastewater to drop suspended particulate
- Parts washer cleaners
- Vibratory deburring wastewater
- Mop and scrubber wastewater
- Paint and ink waters
- Adhesive wash wastewaters
- Dye penetrants bearing waters

## Operating Conditions

Dosing should be determined by jar testing on a 250 mL wastewater sample. A beginning dose for a 250 mL jar test is typically ¼ to ½ gram per 250mL with high speed mixing. This can be increased in increments of 0.5 gm until the desired clarity is obtained. The higher the solids the higher the dose. Dosing per gallon can be 1/2 oz to 4 oz per gallon of wastewater.

Aquapure Quick Drop comes in semi –granular form and is available in 50 lb bags.



WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

---

## Our people. Your problem solvers.

For more information on this process please call us at

1-800-648-3412

or [techservice@hubbardhall.com](mailto:techservice@hubbardhall.com)

