

Demulsifier CC-1

Demulsifier CC-1 is designed to assist in separating water from a wide range of waste oils. This specialized blend of surface-active agents assists in the reduction in water content that increases the value of the oil by creating a more desirable fuel source.

Features & Benefits

Assists in separation of water from oil	Increases value of oil through separation of water
Easy to use, low to no odor	Liquid blend of surface-active ingredients
One product for all oils	Works on: Industrial, fuel and crankcase oils

Typical Applications

Typical oils treated with the Demulsified CC-1 include:

- Industrial Oils
- Fuel Oils
- Crankcase Oils

Operating Conditions

The Demulsifier CC-1 is typically added to a heated storage tank (160°F to 220°F) at a rate of 1 to 2 gallons per 1000 gallon of oil to be treated with good mixing. The treated tank is then allowed to stand without mixing for period (typically 12 to 24 hrs.) to allow the water to be separated to the bottom of the tank. The separated oil then is pumped out of the storage tank leaving a useable fuel oil.



Cleaning
the Hard to Clean



Finishing
the Hard to Finish



Treating
the Hard to Treat

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our people. Your problem solvers.

For more information on this process please call us at
1-800-648-3412
or techservice@hubbardhall.com

